

EMERGENCY LIGHTING

Recessed mounted



888

Wall mounted

Up to 1000lm IP 65




- Maintained / Non-maintained operation
- Autonomous duration 1,5 & 3 hours
- Self-testing
- Waterproof











Recessed Ceiling mounte



European manufacturer



1. W. H.





LED INTERNALLY ILLUMINATED SAFETY SIGNS, SELF-TESTING, WATERPROOF, MAINTAINED/NON-MAINTAINED 220-240V AC/50-60HZ

CHARACTERISTICS	SLL-1001 /WP	SLL-1003 /WP	SLL-501 /WP	SLL-503 /WP	SLL-800/LP/ WP
INSTALLATION	Wall/Ceiling mounted	Wall/Ceiling mounted	Wall/Ceiling mounted	Wall/Ceiling mounted	Wall/Ceiling mounted
MAX. POWER CONSUMPTION	11W/11,4VA	11W/11,4VA	7,8W/8,2VA	7,8W/8,2VA	14,7W/15,2VA
LIGHT OUTPUT (MAINS/EMERGENCY)	700/1000 lm	700/1000 lm	500/500 lm	500/500 lm	800/770 lm
BATTERIES (NiCd)	4.8V/3Ah	2 x 4.8V/3Ah	4.8V/1.5 Ah	4.8V/3 Ah	2 X 4,8V/3Ah
AUTONOMY	1.5 h	3 h	1.5 h	3 h	3 h





ACCESSORIES	Code	Description	
A-1000	927100000	Recess mounting base for SKY LINE	229 gr.
SP-1000	922100000	Double sided PVC 6mm marking panel	500 gr.



Distributor



www.olympia-electronics.gr

T. +30 23530 51200 | F. +30 23530 51486 | info@olympia-electronics.gr